



exact fit seat covers
MADE IN THE USA

To install seat covers – FOR MIDDLE & BACK SEATS

(Allow 45 minutes-1 hour)

WEAR SAFETY GLASSES

There are three ways to remove the bottom of the rear seat if applicable.

1. Unbolt the appropriate bolts to remove.
2. Pull the tabs to release and pull out at an angle.
3. Push seat toward trunk and lift corners at same time (force is needed) The seat will come out like the picture below.
(One retaining bolt may be located at the back).



BOTTOM OF THE SEAT: Fit the cover onto the seat so the front lies flat. Push the flap through the fold in the seat and out the back of the seat. Pull the straps underneath the seat and attach at the front. For the sides, pull the seat edge out a little so you can pass the velcro behind the edge and connect it underneath. (You may want to take the fold-down section off by unbolting it at the base behind the carpet.) Removing the seat may be necessary. If this applies, fit the cover the same as stated above and place back into the vehicle.

BACK OF THE SEAT: To remove back (if necessary), undo bolts at base and lift off of hooks. The seat may hinge forward so removing may not be necessary. Attention to detail is important for a good fit. Connecting all the straps will give you years of trouble-free service. Do not use excessive force to fit. Bring the cover down evenly on each side and make sure the headrest opening is lined up. Slowly work the fabric over the seat, as the foam backing will tend to grip the original factory upholstery. Slide your hand down the material and guide it into the seats contours. This will encourage the material to create a snug, exact fit. Find the cover that matches each seat shape. Push the bottom flap at the front through the fold in the seat and connect the flap at the seat's back. Connect the shock cords.

NOTE: If there are integrated seatbelts you **MUST** slide the seat cover between the seat belt and the seat cushion and then proceed with the appropriate attachments.

BOLSTERS: (If applicable) After removing the seat bottom, a single bolt will be revealed. Remove the bolt and lift up. Apply the bolster cover. To reinstall, insert the top first and slide down. There is a plastic strip that slides into a metal sleeve. Some bolsters attach with velcro and foam tube and do not need to be removed. Place the tubing between the cushion and plastic framing. Attach the Velcro to the original fabric.

CLEANING: MACHINE WASH (FRONT LOAD GENTLE CYCLE ONLY) HANG DRY,
(for stains, follow upholstery cleaner instructions).

FOR ADDITIONAL INSTALL ASSISTANCE PLEASE CONTACT US